



TROUBLE SHOOTING INFORMATION

TACHOMETERS, SPEEDOMETERS FOR 2000-2003 CORRECT CRAFT

Veethree no longer offers or services the digital tachometer or speedometer used in 2000-2003 model year Correct Craft.

However, the Sierra Premier Pro Series gauges* will operate well in the same dash panel application. The gauges have a fog resistant coating on the inside of the lens, sealed against water intrusion from rain or normal wash down, have domed lens to prevent standing water, and the bezel is black.

The instrument dial lights red and the pointer lights bright white at night for excellent visibility.

The tachometer is available in 6000 or 8000 RPM. It will use the same tachometer wires in the boat now. The plug does need to be removed from the tachometer harness and ring terminals installed on the wire ends to connect to the new tachometer.

62724P - 6000 RPM
62725P - 8000 RPM

The speedometer is available in 65 MPH or 50 MPH. It will use one of the pitots on the transom. Bypass the Speedometer Electric Module. You will not need it, or the speedometer wiring harness. Since the speedometer has only the light that is electrical, you can jump those two connections from the tachometer.

62722P - 65 MPH
84510F - 50 MPH** (Special Order only)

There is now a 60 MPH GPS speedometer option available. The GPS speedometer does require a speed signal from an NMEA0183 device or an NMEA0183 GPS receiver (sold separately).

781-627-060P - 60MPH GPS speedometer
68982P - 4 foot harness, low speed (1 Hz), updates once (1) every second
69053P - 4 foot harness, high speed (10 Hz), updates ten (10) times every second
68755P - 25 foot harness, low speed (1 Hz), updates once (1) every second

These quality products are available from retailers such as West Marine, Boater's World, Bass Pro, etc. We are certain these gauges will work well in your boat.

*Not approved for National Water Ski Association competition events.

**For special orders, please email Sierra Marine at lit-marinecs@dometic.com to ask for a retailer which can special order this gauge for you.

PREMIER PRO - A very popular OEM line, Premier features black dials with modern white and blue graphics. When lighted, white dial grads become red and pointer lights white. These instruments feature automotive type light-piping and a fog-resistant design for outstanding readability.



FEATURES:

- Full automotive type lighting, no "halo" around dial edges. When lit, white dial grads become red, pointer lights white.
- Black dial, white graduations/numerals (metrics in blue), white pointer staff.
- Scratch resistant curved glass lenses, with black, near-flush bezels.
- U.S. and metric scales, with ISO symbols, where appropriate.
- Optional add-on eyebrow or square bezels available (See Gauge Accessories for details).
- Line includes standard ignition engine synchronizer kits including module.
- Fog-Resistant Design! Complies with SAE J-1810.

SELECTION GUIDE:

GAUGE DESCRIPTION	SIZE	DIAL RANGE	SENDER CODE	PART NUMBER
Fuel Gauge:	2"	E-1/2-F	REQUIRES "F"	62718P •
Hourmeter:	2"	10,000 Hrs.	NONE REQUIRED	62719P •
Oil Pressure Gauge (Electric):				
Oil Pressure 80 PSI	2"	0-80 PSI	REQUIRES "C"	62720P •
GPS Speedometer:				
35 MPH	3"	0-35 MPH	GPS RECEIVER	781-627-035P
60 MPH	3"	0-60 MPH	GPS RECEIVER	781-627-060P
80 MPH	3"	0-80 MPH	GPS RECEIVER	781-627-080P •
120 MPH	3"	0-120 MPH	GPS RECEIVER	781-627-120P
Speedometer Kits:				
65 MPH (Pitot type)	3"	10-65 MPH	INCLUDES "G"	62722P •
80 MPH (Pitot type) Head Only	3"	20-80 MPH		62723PH
Tachometers (Electric):				
O/B & 4-Stroke Gas Engines*	3"	0-6000 RPM	O/B ALT./COIL	62724P •
O/B & 4-Stroke Gas Engines*	3"	0-8000 RPM	O/B ALT./COIL	62725P •
Trim Gauges (Outboard, I/O):				
Johnson/Evinrude (All) & Suzuki 4-stroke 2002 & Up	2"	UP-DOWN	BY ENG. MFR	62726P •
Mercury O/B & I/O, Mariner, Force, Cobra,				
Volvo DP & SX, Yamaha 2001 & Up	2"	UP-DOWN	BY ENG. MFR	62727P •
Yamaha Outboards pre-2001	2"	UP-DOWN	BY ENG. MFR	62728P •
Voltmeter-12 Volt:	2"	8-16 VDC	NONE REQUIRED	62730P •
Water Pressure Kit (Outboard):** (Each kit includes fittings and 20 feet of tubing)	2"	30 PSI	INCLUDES "WP"	62721P •
Water Temp. Kit (Outboard):** (For all electric-start outboards)	2"	COLD-HOT	INCLUDES "J"	62748P •
Water Temp. Gauge (I/O, I/B):	2"	120-240°F	REQUIRES "D"	62729P •
Instrument Set "INBOARD/STERNDRIVE"	Contains: 62724P, 62722P, 62718P, 62730P, 62729P, 62720P			62715P •

• Display Packaged Item

* Not tested for complete aftermarket ignition systems, will work with aftermarket replacement parts.

** Adapter (P/N 61886P) is required for Yamaha.
Use 4000 RPM tachometer or lower for diesel applications.